



P/N	LENGTH	AWG
SA-8882-HDD-.5M	500±25	HITACHI 30AWG
SA-8882-HDD-1M	1000±30	HITACHI 30AWG

MATERIAL RoHS COMPLIANT:

CABLE:

ELECTRICAL:

DIFFERENTIAL IMPEDANCE TDR: 100+/-5 OHMS

CAPACITANCE: 47 pF/m nom.

SKEW(within the pair-3m sample): 8 ps/m max

COMPONENT:

CONDUCTOR: 30 AWG SOLID TINNED COPPER .010" NOM. OD

APPROVALS:

UL AWM VW-1 80°C 30V, RoHS COMPLIANT, HITACHI

CONNECTOR:

P0: Mini SAS 4x CABLE PLUG - 26CKT CONNECTOR (SFF-8088)

(1) P.C.B: FR4, 4 LAYERS

(2) LATCH: STAINLESS STEEL

(3) BACKSHELL: ZINC DIE CASTING HOOD/ NICKEL PLATING

(4) WITH EXTERNAL UNIVERSAL KEY

P1~P2 SAS DRIVE CABLE RECEPTACLE (SFF-8482)

P3~P4 4PIN POWER MALE CONNECTOR

POWER CABLE: UL 1007 18AWG 80°C 300V



P/N: SA-8882-HDD-XX Desc. : MiniSAS (SFF-8088) - HDD (SFF-8482) female, 2x